



### IMPORTANT

Disconnect power before installing fixtures. Read instructions before starting work. This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

## Orchestra Circle 2756A/A2 LED Series

### POST ARM INSTALLATION INSTRUCTIONS

- 1 Remove luminaire components from cartons.
- 2 Attach LED driver tray to end cap assembly through key holes and tighten hex nuts provided.
- 3 Remove end cap screws (2) from end cap assembly.
- 4 Remove pole fitter cap screws (3) and pole fitter cap if necessary to access wire from arm assembly.
- 5 Slide head assembly on to arm assembly / post fitter assembly. Feed the supply wire leads through arm assembly and out bottom of fitter tube. Re-attach end cap screws (2) removed in step 3. Be careful not to pinch wires from head assembly.
- 6 Repeat step 5 for double head arm units (2756A2).
- 7 Connect the black, white and green wire leads from LED driver to the supply leads from the pole. Tuck the wires down into the pole top. Be careful not to pinch wires when placing assembly on to pole.
- 8 Place complete assembly over pole top. Orchestra head facing down as per specification page and diagram. Secure to pole with set screws (3) that are provided on post top fitter.
- 9 Reflector disks (2) are attached with hardware provided at the top location as per diagram.
- 10 Energize and test as required.
- 11 This fixture is supplied with an LED as specified for the project and is self contained.