

# Saturna 4007ALED Maxi Cantilevered Arm Streetscape Post Mount EXTERIOR


MODEL	LED	COLOR TEMPERATURE	VOLT	LENS	OPTIONS	COLOUR
4007A	1x16L <i>LED module</i> 16 watt	40* <i>4000K</i> 1700 lumens <sup>1</sup>	120*	RF* <i>frost</i>	FS <i>fusing</i>	WT <i>white texture</i>
			208			BT <i>black texture</i>
			240			SM <i>silver metallic</i>
			277			AN <i>aluminum natural</i>
			347			BZ <i>bronze</i>
						GM <i>gunmetal</i>
						WS <i>white satin</i>
						BM <i>black matte</i>
						RAL <i>specify no.</i>

\*Standard configuration unless otherwise specified <sup>1</sup>Delivered lumens (4000K, 80 CRI)

SAMPLE CATALOG NUMBER: 4007A - 1x16L - 40 - 120 - RF - WT

Using this catalog number would order 1 model 4007A post arm luminaire with a 16 watt, 4000K, 1700 lumen light engine wired to 120 volts, with a frosted glass globe, painted white texture. Poles are supplied separately.

CONSTRUCTION	MOUNTING	OPTICAL	PROTECTION
<p>Materials Driver housing / Arm assembly / Mast: Heavy aluminum tubing. Luminaire housing: Cast aluminum. Gasket: EPDM rubber. Strut assembly: Aluminum plate, keyholed removal. Reflector disks: Aluminum plate. Lens/diffuser: Threaded, tempered glass.</p> <p>LED Components Driver: Constant current, 450mA. Light Engine: Chip-on-Board 13mm LES, Zhaga Book 3 Compliant Socket</p>	<p>This luminaire is designed to mount to a bottleneck pole catalog number 3031 with a 3.5" diameter x 4.5" tall tenon. Driver is mounted in the base of the pole. Arm assembly and head are locked to the pole with three stainless set screws.</p>	<p>The 4007A series is a Type V area distribution, non-cutoff classified product. The frosted glass diffuser softens the light. Strut and disk assembly shield light source. Top reflector disk controls upward light.</p>	<p>The Saturna maxi cantilevered arm mount post luminaire is listed for use in wet locations to UL and CSA Standards. Windloading EPA = 1.63 Sq. Ft. LED life: 50,000 hours minimum, L70 @ 25°C.</p>



## Saturna 4007ALED Detailed Product Description

- |   |   |   |   |
|---|---|---|---|
| 1 | Cantilevered Arm Assembly - Aluminum 4.5" Fitter      | 6 | Lens/Diffuser - Frosted Glass Threaded - Tempered |
| 2 | Housing - Cast Aluminum                               | 7 | Strut Assembly - Keyholed Removal .125" Aluminum  |
| 3 | Gasket - E.P.D.M. Rubber                              | 8 | Driver, 450mA, 120-277 Volt Input                 |
| 4 | Reflector Disks .125" Aluminum                        | 9 | Pole (Not Included - Order Separately) Ø4.0"      |
| 5 | Chip-on-Board 13mm LES, Zhaga Book 3 Compliant Socket |   |   |